













Legacy® ANSI • CE • UKCA • CSA •

Integrated side shields provide additional protection
 // Lightweight spectacle – 23 gm // Custom
 imprinting available

Lens and Temples | 6 Variations

-  ES10910S  Clear
-  ES10910STM  Clear **H2MAX AF**
-  ES10920S  Gray
-  ES10920STM  Gray **H2MAX AF**
-  ES10950SF  5.0 IR Filter
-  ES10960SF  3.0 IR Filter



Part No.	Lens Marking	Temple Marking	Measurements	Materials
ES10910S	2C-1.2 P 1FT CE	CE P EN166 FT UKCA	Weight: 23 gm	Lens: polycarbonate
ES10910STM	2C-1.2 P 1FT KN CE	CE P EN166 FT UKCA	PD: 64 mm	Nosepiece: polycarbonate
ES10920S	5-2.5 P 1FT CE	CE P EN166 FT UKCA	Bridge: 10.7 mm	Side Shield: polycarbonate
ES10920STM	5-2.5 P 1FT KN CE	CE P EN166 FT UKCA	Lens base: 6 curve	Temples: polycarbonate
ES10950SF	3 P 1F CE	CE P EN166 FT UKCA	Lens size diagonal: 51.5 mm	Screw: stainless steel
ES10960SF	5 P 1F CE	CE P EN166 FT UKCA	Lens size vertical: 46 mm	

Lens Marking Symbols

Code - field of use

2 or 3: UV filter

5 or 6: Solar filter

Colour Perception

C: Unimpaired colour perception

Protection Class

1.2 - 6: Degree of visible light filtration

Optical Class

1: High optical quality - no optical distortion

Mechanical Strength

F: Low energy impact, resists a 6 mm, .86 g at 45 m/s

T: Impact protection at extreme temperature conditions

Symbols

P: Manufacturer's mark

K: Resistance to surface damage by fine particles

N: Filter with anti-fog

CE: Certification of the European Union

Temple Marking Symbols

Symbols

CE: Certification for European Union

P: Manufacturer's mark

EN166: Standard for protective eyewear

UKCA: Certification for United Kingdom

Mechanical Strength

F: Low energy impact

T: Impact protection at extreme temperature conditions

Measurements

Weight: 23 gm

PD: 64 mm

Bridge: 10.7 mm

Lens base: 6 curve

Lens size diagonal: 51.5 mm

Lens size vertical: 46 mm

Lens thickness: 2 mm

Overall length (lens - tip): 155 mm

Overall width (hinge - hinge): 136 mm

Closest point between temple tips: 98.3 mm

Closest point between lens: 20.3 mm