

Cappture Pro ANSI • CE • CSA •



DIELECTRIC



INCLUDES STRAP



DROPLET AND SPLASH TEST



DUST TEST

Dielectric // Fits over most prescription glasses // Flexible rubber gasket // Full strap with quick release // Passes D3: Droplet and Splash Test // Passes D4: Dust Test

Rubber Gasket with Strap | 2 Variations

- EGG9910TM ● ● Clear H2MAX AF
- EGG9920TM ● ● Gray H2MAX AF



Part No.	Lens Marking	Temple Marking
EGG9910TM	2C-1.2 P 1FT KN CE	CE P EN166 FT 3 4
EGG9920TM	5-2.5 P 1FT KN CE	CE P EN166 FT 3 4

General Specifications
Weight: 66.2 gm
PD: 64 mm
Bridge: 31 mm
Lens base: 2.5 curve
Lens size diagonal: 144 mm
Lens size vertical: 52.2 mm
Lens thickness: 2.0 mm
Overall length: 92 mm
Overall width: 178 mm

Materials
Lens: polycarbonate
Rubber gasket: polycarbonate & thermoplastic rubbers (TPR)
Nosepiece: polycarbonate
Strap holder: nylon
Headband: polyester & polyoxymethylene

Lens Marking Symbols
Code - field of use
2 or 3: UV filter
5 or 6: Solar filter
Colour Perception
C: Unimpaired colour perception
Protection Class
1.2 - 6: Degree of visible light filtration
Optical Class
1: High optical quality - no optical distortion
Mechanical Strength
F: Low energy impact, resists a 6 mm, .86 g at 45 m/s
T: Impact protection at extreme temperature conditions
Symbols
P: Manufacturer's mark
K: Resistance to surface damage by fine particles
N: Filter with anti-fog
CE: Europe standard

Temple Marking Symbols
Symbols
CE: Europe standard
P: Manufacturer's mark
EN166: CE specification for protective eyewear
3: Droplets or splashes of liquids
4: Large dust particles
Mechanical Strength
F: Low energy impact
T: Impact protection at extreme temperature conditions