

ALAIR®

FASHIONABLE ECONOMY SPECTACLE



| PART | LENS |
|-------------|---|
| ES3210S** | <input type="checkbox"/> Clear |
| ES3210ST*** | <input type="checkbox"/> Clear (Anti-Fog) |
| ES3220S** | <input checked="" type="checkbox"/> Gray |
| ES3230S** | <input type="checkbox"/> Amber |
| ES3260S** | <input type="checkbox"/> Infinity Blue |

- Economically priced to fit any budget.
- Incredibly light, resilient & durable protective eyewear for all day wear.
- Closefitting unitary front with dual 9.5 base curvature offers wide and unobstructed vision.
- Fashionable design resembles sunglasses, suitable for both men and women.
- Scratch-resistant, hard-coated polycarbonate lens filter out more than 99.9% of harmful UV rays.






| GENERAL SPECIFICATION |
|---|
| Bridge: 12mm |
| Closest Point Between Lens: 8mm |
| Closest Point Between Temple Tips: 84mm |
| Lens Base: 9.5 Curve |
| Lens Size Diagonal: 73mm |
| Lens Size Vertical: 42mm |
| Lens Thickness: 2.45mm |
| Overall Length (Lens-Tip): 158mm |
| Overall Width (Hinge-Hinge): 134mm |
| PD: 68mm |
| Weight: 22gm |

ALAIR®

FASHIONABLE ECONOMY SPECTACLE

| PACKAGING |
|-------------------|
| Polybag: 1 pc |
| Inner Box: 12 pcs |
| Case: 300 pcs |

| COMPONENT | MATERIAL | FEATURES |
|--------------|-----------------|---|
| Lens | Polycarbonate | 9.5 curve lens, wrap around design with side protection |
| Frame | N/A | N/A |
| Side Shields | Polycarbonate | Integral to lens |
| Nose Piece | Polycarbonate | Universal, integral to lens |
| Temple | Polycarbonate | Spatula |
| Hinge | Polycarbonate | 3 barrel type, integral to frame/sleeve |
| Screw | Stainless Steel | Standard hinge screw |

| PART | LENS | LENS MARKING | FRAME MARKING |
|----------|---|---------------------|---------------|
| ES3210S |  Clear | 2C - 1.2 P 1 F CE | CE P EN166 F |
| ES3210ST |  Clear | 2C - 1.2 P 1 F N CE | CE P EN166 F |
| ES3220S |  Gray | 5 - 2.5 P 1 F CE | CE P EN166 F |
| ES3230S |  Amber | 2 - 1.2 P 1 F CE | CE P EN166 F |
| ES3260S |  Infinity Blue | 2C - 1.4 P 1 F CE | CE P EN166 F |

LENS MARKING

Code (field of use):

2 or 3: UV Filter
5 or 6: Solar Filter

Color Perception:

C: Unimpaired color perception

Protection Class:

1.2 to 6: Degree of visible light filtration

Optical Class:

1: High optical quality / No optical distortion

Mechanical Strength:

S: Extra strong, resists a 22mm, 43g ball falling 1.30 m/s
F: Low energy impact, resists a 6mm, 0.86g at 45 m/s
B: Medium energy impact, resists a 6mm, 0.86g at 120 m/s
A: High energy impact, resists a 6mm, 0.86g at 190 m/s

Symbols:

P: Manufacture Indication
N: Filter with Anti-Fog features
CE: European Standard

FRAME MARKING

Symbols:

CE: European Standard
P: Manufacture Indication
EN166: CE specification for protective eyewear

Mechanical Strength:

F: Low energy impact
B: Medium energy impact
BT: Medium energy impact at extreme temperatures

Protection Class:

3: Protection against liquid droplets
4: Protection against large dust